The Network Industry's First 100G Packet Capture Appliance



Capture 100% / Replay 100%

BENEFITS

- Improve customer experience
- ✓ Prevent loss of business due to network downtime
- ✓ Insure network infrastructure vendors have complete data for troubleshooting
- ✓ Extend the value of existing network tools with automated actions
- Reduce network operating cost with better team collaboration and efficiency

SYNESIS is a network data recorder that can continuously capture up to **100Gbps**. SYNESIS, being an all-in-one packet capture system, is easily deployed in data centers, remote site branches, and test labs as a physical appliance. Configuration is minimal so it can be installed and capturing high speed traffic in minutes.

Existing network tools just can't keep up with today's traffic rates caused by increased user demand for bandwidth intensive applications. The result - oversubscription of tools which leads to misdiagnosis. Only **SYNESIS** is able to capture all network packet data completely and at high granularity.

HIGHLIGHTS

- ✓ Industry's first Zero Packet-Loss Full Duplex Stream-to-Disk Solution up to 100Gbps
- ✓ Support for 1G/10G/40G/100G interfaces
- Storage capacity configurations from 5TB to 300TB (Optional)
- ✓ Web browser based Protocol Analyzer with realtime decode.
- Wireshark analyzer can be installed as a plugin
- Open Architecture with REST
- Built-in Network and Application performance analytic engines
- ✓ Strong data indexing provides fast packet retrieval from storage
- ✓ Detect microburst traffic in 100 microsec intervals
- ✓ Available as complete turn-key system
- ✓ Multi-TB captured packets playback in microsecond level allowing to replay microburst traffic
- ✓ Packets can be edited before sending to network

Now with Replayer!

Replay single packets or data from extended long term capture sessions. Perfect application for R&D/QA and Field Support teams!

Capture 100% of network traffic in the field!




...then Replay 100% in the lab!



*Replayer availability based on model

Packet Capture



Application Performance Monitoring Support




Figure 1: APM and NPM analysis

Intelligent Report Builder



Figure 2: Intelligent report engine with drag and drop ability

SYNESIS is a capture appliance compatible with 10M/100M/1G/10G/100G networks that can capture traffic at wire speed without data loss. A backup function allows saving to PCAP files automatically while capturing. The storage destination can either be a local or remote file system.

By using the capture indexing function, the KPI (Key Performance Indicator) network status can be ascertained at a trend level basis.

Users can build reports by using drag -and -drop with modular graphic components and predefined templates. The reports can be created daily, weekly and monthly with auto notification function.

Customized and Profiling Dashboard



Figure 3: Customized and Profiling Dashboard

Packet Replayer

de Liefe		Syseet's Packetilepiaper		
-Savnesis Sy	and Deal	-tD - stars		
	ilesis Paci	erkepiayer		
Setting Peplay				
😥 Lasimi	ted			
Section				
		upper lost of the file size		
P Part 0	- Fées	Prometroyopcophendigeap		Select
	nevrta	With Newto New	Use this rules for all	1011
	FCS	C overwrite PCS	C Appendires	ill flow
Ci Part (0	. ries			Select
	Revite	wite flevete fules		100
Receivers	10.5	O Overwrite FCS	# Append FCS	CO Marc
C Part (C)	1 140			Salest
	9) (Ö			Select
	PC5	C henseve FCS (Porcity remove the last 4 lastes)		H For
D Pert. (0 🔍	100			Select
	PCS	A C Remove FCS (Forcibly remove the last 4 bytes)		iii Raw
			mapley.	574.0
Status Rurring part=0 repeat-			Pepley	5740

trend information for each selected agent.
Each user will have their own dedicated
configurable dashboards display which also
allows customization on display widget and
page level.
Any dashboards added or removed are user
base. Multiple dashboard profiles are supported

The Dashboard is a page that displays real-time

Real-life Wire-rate Traffic capture and replay up to 100Gbps with micro-second level packet gap granularity. the following items can be replaced from the packet header within the PCAP file. -MAC address -VLAN ID -IP address (v4/v6)