

水耕自動栽種控制系統

建議售價：100,000元



單板編號: 255		選擇要設定模式 A B C D			
■ 離電器 (1)		■ 紅, 藍, 白 調光設定			
植物溫度(度C)	10.0	時辰	紅光強	藍光強	白光強
正負值(度C)	1.0	0	0	0	0
開光間(秒)	600	1	0	0	0
開光間(秒)	300	2	0	0	0
■ 離電器 (2&3)		■ 植物溫度 自動調整			
植物溫度(度C)	10.0	時辰	紅光強	藍光強	白光強
正負值(度C)	1.0	6	50	50	50
開光間(秒)	600	7	70	85	85
開光間(秒)	300	8	90	95	90
■ 其他功能 =>		9	95	95	95
		10	10	50	30
		11	95	95	95
		12	0	0	0
		13	95	95	95
		14	95	95	95
		15	90	95	90
		16	70	85	85
		17	50	50	50
		18	30	35	30
		19	20	20	20
		20	10	50	30
		21	0	0	0
		22	0	0	0
		23	0	0	0



栽種程序分為**手動調光及自動調光**
使用人機介面自動管理(離線自動控制)**光照及營養液的循環**
可控制三迴路燈板(RBW)一天**可分成24段控制**
智能控制(**育苗/栽種/採收/節能**) 四種模式自動選擇
連接**APP或PC**，可即時調整變更參數

